

US007760917B2

(12) **United States Patent**
Vanhoucke et al.

(10) **Patent No.:** **US 7,760,917 B2**
(45) **Date of Patent:** **Jul. 20, 2010**

(54) **COMPUTER-IMPLEMENTED METHOD FOR PERFORMING SIMILARITY SEARCHES**

(58) **Field of Classification Search** None
See application file for complete search history.

(75) Inventors: **Vincent Vanhoucke**, Menlo Park, CA (US); **Salih Burak Gokturk**, Mountain View, CA (US); **Dragomir Anguelov**, San Francisco, CA (US); **Kuang-chih Lee**, Union City, CA (US); **Munjal Shah**, Palo Alto, CA (US); **Ashwin Tengli**, Bangalore (IN)

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,296,945	A	3/1994	Nishikawa et al.	
5,450,504	A *	9/1995	Calia	382/118
5,734,749	A	3/1998	Yamada et al.	
5,781,650	A *	7/1998	Lobo et al.	382/118
5,845,639	A	12/1998	Hochman et al.	
5,982,912	A	11/1999	Fukui et al.	
6,035,055	A *	3/2000	Wang et al.	382/118
6,173,068	B1	1/2001	Prokoski	
6,353,823	B1	3/2002	Kumar	

(Continued)

FOREIGN PATENT DOCUMENTS

JP 2002-328925 11/2002

(Continued)

OTHER PUBLICATIONS

U.S. Appl. No. 12/395,422, filed Feb. 27, 2009, Gokturk et al.

(Continued)

(73) Assignee: **Like.com**, San Mateo, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **11/777,070**

(22) Filed: **Jul. 12, 2007**

(65) **Prior Publication Data**

US 2008/0080745 A1 Apr. 3, 2008

Related U.S. Application Data

(63) Continuation-in-part of application No. 11/246,742, filed on Oct. 7, 2005, and a continuation-in-part of application No. 11/246,741, filed on Oct. 7, 2005, and a continuation-in-part of application No. 11/246,589, filed on Oct. 7, 2005, and a continuation-in-part of application No. 11/246,434, filed on Oct. 7, 2005.

(60) Provisional application No. 60/807,120, filed on Jul. 12, 2006, provisional application No. 60/679,591, filed on May 9, 2005.

(51) **Int. Cl.**
G06K 9/00 (2006.01)

(52) **U.S. Cl.** **382/115**


Primary Examiner—Charles Kim

(74) *Attorney, Agent, or Firm*—Mahamedi Paradice Kreisman LLP

(57) **ABSTRACT**

A similarity search may be performed on the image of a person, using visual characteristics and information that is known about the person. The search identifies images of other persons that are similar in appearance to the person in the image.

9 Claims, 3 Drawing Sheets



U.S. PATENT DOCUMENTS

6,397,219	B2	5/2002	Mills	
6,418,430	B1	7/2002	DeFazio et al.	
6,427,020	B1	7/2002	Rhoads	
6,546,185	B1	4/2003	Kim et al.	
6,556,713	B2	4/2003	Kobayashi et al.	
6,606,417	B1	8/2003	Brechner	
6,785,421	B1	8/2004	Gindele et al.	
6,801,641	B2	10/2004	Eraslan	
6,819,783	B2	11/2004	Goldberg et al.	
6,919,892	B1	7/2005	Cheiky et al.	
6,925,197	B2	8/2005	Dimitrova et al.	
7,006,236	B2	2/2006	Tomasi et al.	
7,140,550	B2	11/2006	Ramachandran	
7,203,356	B2	4/2007	Gokturk et al.	
7,310,431	B2	12/2007	Gokturk et al.	
7,340,077	B2	3/2008	Gokturk et al.	
7,382,903	B2	6/2008	Ray	
7,519,200	B2	4/2009	Gokturk et al.	
7,542,610	B2	6/2009	Gokturk et al.	
2001/0033690	A1*	10/2001	Berche et al.	382/192
2002/0097893	A1	7/2002	Lee et al.	
2002/0103813	A1	8/2002	Frigon	
2002/0107718	A1	8/2002	Morrill et al.	
2002/0114522	A1	8/2002	Seeber	
2002/0187774	A1	12/2002	Ritter et al.	
2003/0028451	A1	2/2003	Ananian	
2003/0063778	A1*	4/2003	Rowe et al.	382/115
2003/0063779	A1	4/2003	Wrigley	
2003/0169906	A1	9/2003	Gokturk et al.	
2003/0195901	A1	10/2003	Shin et al.	
2003/0202683	A1	10/2003	Ma et al.	
2004/0003001	A1	1/2004	Shimura	
2004/0264810	A1	12/2004	Taugher et al.	
2005/0002568	A1	1/2005	Chupeau et al.	
2005/0078885	A1	4/2005	Ozaki et al.	
2005/0094897	A1	5/2005	Zuniga	
2005/0111737	A1*	5/2005	Das et al.	382/190
2005/0271304	A1	12/2005	Retterath et al.	
2006/0097988	A1	5/2006	Hong	
2006/0133699	A1	6/2006	Widrow et al.	
2006/0143176	A1	6/2006	Mojsilovic et al.	
2006/0173560	A1	8/2006	Widrow et al.	
2006/0227992	A1	10/2006	Rathus et al.	
2006/0251292	A1	11/2006	Gokturk et al.	
2006/0251338	A1	11/2006	Gokturk et al.	
2006/0253491	A1	11/2006	Gokturk et al.	
2007/0003113	A1	1/2007	Goldberg	
2007/0258645	A1	11/2007	Gokturk et al.	
2008/0082426	A1	4/2008	Gokturk et al.	
2008/0144943	A1	6/2008	Gokturk et al.	
2008/0152231	A1	6/2008	Gokturk et al.	
2008/0177640	A1	7/2008	Gokturk et al.	
2008/0199075	A1	8/2008	Gokturk et al.	
2008/0212849	A1	9/2008	Gao	
2008/0212899	A1	9/2008	Gokturk et al.	
2009/0034782	A1	2/2009	Gering	
2009/0177628	A1	7/2009	Yanagisawa et al.	
2009/0196510	A1	8/2009	Gokturk et al.	
2009/0208116	A1	8/2009	Gokturk et al.	

FOREIGN PATENT DOCUMENTS

JP	2003-216866	A	7/2003
JP	2004-220074	A	8/2004
JP	2006-119836		11/2006
KR	1020070077908	A	7/2007

OTHER PUBLICATIONS

U.S. Appl. No. 12/431,706, filed Apr. 28, 2009, Gokturk et al.
 Final Office Action dated Jun. 16, 2009 for U.S. Appl. No. 11/936,705, 20 Pages.

Final Office Action dated Aug. 11, 2008 for U.S. Appl. No. 11/246,741, 18 Pages.
 Final Office Action dated Oct. 20, 2008 for U.S. Appl. No. 11/543,758, 7 Pages.
 International Preliminary Report on Patentability and Written Opinion of the International Searching Authority in Application PCT/US2006/018016, Oct. 16, 2008, 12 pages.
 International Preliminary Report on Patentability in Application PCT/US2006/038864, Nov. 27, 2008, 10 pages.
 International Preliminary Report on Patentability and Written Opinion of the International Searching Authority in Application PCT/US2007/083935, May 22, 2009, 20 pages.
 International Search Report and Written Opinion of the International Searching Authority in Application PCT/US06/18016, U.S. International Searching Authority, Jun. 17, 2008, 17 pages.
 International Search Report and Written Opinion of the International Searching Authority in Application PCT/US06/38864, U.S. International Searching Authority, Oct. 14, 2008, 16 pages.
 International Search Report and Written Opinion of the International Searching Authority in Application PCT/US07/83935, U.S. International Searching Authority, Aug. 18, 2008, 23 pages.
 Non-Final Office Action dated Dec. 29, 2008 for U.S. Appl. No. 11/246,589, 19 Pages.
 Non-Final Office Action dated Oct. 21, 2008 for U.S. Appl. No. 11/936,705, 18 Pages.
 Non-Final Office Action dated Oct. 27, 2008 for U.S. Appl. No. 11/246,434, 11 Pages.
 Non-Final Office Action dated Oct. 27, 2008 for U.S. Appl. No. 11/936,734, 7 Pages.
 Non-Final Office Action dated Dec. 30, 2008 for U.S. Appl. No. 11/936,713, 15 Pages.
 Non-Final Office Action dated Dec. 6, 2007 for U.S. Appl. No. 11/246,741, 31 Pages.
 Non-Final Office Action dated Jun. 3, 2008 for U.S. Appl. No. 11/246,742, 16 Pages.
 Non-Final Office Action dated Jun. 6, 2008 for U.S. Appl. No. 11/543,758, 13 Pages.
 Non-Final Office Action dated May 28, 2009 for U.S. Appl. No. 11/246,434, 6 Pages.
 Notice of Allowance dated Dec. 22, 2008 for U.S. Appl. No. 11/246,742, 12 Pages.
 Notice of Allowance dated Apr. 17, 2009 for U.S. Appl. No. 11/543,758, 14 Pages.
 Tu, Zhuowen et al., "Image Parsing: Unifying Segmentation, Detection, and Recognition," Proceedings of the Ninth IEEE International Conference on Computer Vision (ICCV 2003), University of California, Los Angeles, Los Angeles, CA 90095, 7 pages.
 Yuille, A.L. et al, "Signfinder: Using Color to detect, localize and identify informational signs," Proceedings International Conference on Computer Vision, ICCV, 1998, Smith-Kettlewell Eye Research Institute, 2318 Fillmore Street, San Francisco, CA 94115, 9 pages.
 Final Office Action dated Oct. 27, 2009 for U.S. Appl. No. 11/246,741, 20 Pages.
 Final Office Action dated Jun. 30, 2009 for U.S. Appl. No. 11/246,589, 13 Pages.
 Non-Final Office Action dated Dec. 15, 2009 for U.S. Appl. No. 12/395,422. 10pages.
 Non-Final Office Action dated Dec. 2, 2009 for U.S. Appl. No. 11/246,589. 14pages.
 Non-Final Office Action dated Sep. 30, 2009 for U.S. Appl. No. 12/431,706. 9 pages.
 Non-Final Office Action dated Sep. 14, 2009 for U.S. Appl. No. 11/246,434. 11 pages.
 Non-Final Office Action dated Apr. 7, 2009 for U.S. Appl. No. 11/246,741, 21 Pages.
 Notice of Allowance dated Sep. 17, 2009 for U.S. Appl. No. 11/936,705 14 Pages.
 Notice of Allowance dated Sep. 28, 2009 for U.S. Appl. No. 11/936,713, 15 Pages.
 Notice of Allowance dated Oct. 1, 2009 for U.S. Appl. No. 11/936,734, 12 Pages.

Action Closing Prosecution mailed Apr. 26, 2010 for U.S. Appl. No. 95/001,307; 20 pages.

Final Office Action mailed May 12, 2010 for U.S. Appl. No. 12/431,706; 12 pages.

Gangopadhyay, Aryya, "An image-based system for electronic retailing", Decision Support Systems 32, 2001, Department of Information Systems, University of Maryland Baltimore County, 1000 Hilltop Circle, ACIV 481, Baltimore, MD 21250, 10 pages.

International Search Report and Written Opinion mailed Feb. 24, 2010 in PCT/US2009/050600 13 pages.

Lii, Yi et al., "Object Recognition for Content-Based Image Retrieval", Department of Computer Science and Engineering, University of Washington, Seattle, WA 98195-2350, Jan. 2002, 21 pages.

Liu, James et al., "Smart Shopper: An Agent-Based Web-Mining Approach to Internet Shopping," IEEE Transactions on Fuzzy Systems, vol. 11, No. 2, Apr. 2003, 12 pages.

Notice of Allowance dated Feb. 22, 2010 for U.S. Appl. No. 11/246,343. 6pages.

Order Granting/Denying Request for Inter Parts Reexamination mailed Apr. 26, 2010 for U.S. Appl. No. 95/001,30; 15 pages.

Replacement Request for Ex Parte Reexamination dated Mar. 18, 2010 for U.S. Appl. No. 95/001,307, 145 pages.

Wang, James et al., "SIMPLiCity: Semantics-Sensitive Integrated Matching for Picture Libraries" IEEE Transactions on Pattern Analysis and Machine Intelligence, vol. 23, No. 9, Sep. 2001, 17 pages.

* cited by examiner




FIG. 1





FIG. 2

**FIG. 3**

1

COMPUTER-IMPLEMENTED METHOD FOR PERFORMING SIMILARITY SEARCHES

RELATED APPLICATIONS

This application claims benefit of priority to U.S. Provisional Patent Application No. 60/807,120, entitled METHOD FOR ASSESSING FACE SIMILARITY THAT LEVERAGES BIOGRAPHICAL CUES, filed Jul. 12, 2006, the aforementioned priority application being hereby incorporated by reference in its entirety.

This application is a continuation-in-part of U.S. patent application Ser. No. 11/246,742, entitled SYSTEM AND METHOD FOR ENABLING THE USE OF CAPTURED IMAGES THROUGH RECOGNITION, filed on Oct. 7, 2005; which claims benefit of priority to U.S. Provisional Patent Application No. 60/679,591, entitled METHOD FOR TAGGING IMAGES, filed May 9, 2005; both of the aforementioned priority applications being hereby incorporated by reference in their entirety.

This application is a continuation-in-part of U.S. patent application Ser. No. 11/246,741, entitled SYSTEM AND METHOD FOR ENABLING SEARCH AND RETRIEVAL FROM IMAGE FILES BASED ON RECOGNIZED INFORMATION, filed Oct. 7, 2005; which claims benefit of priority to U.S. Provisional Patent Application No. 60/679,591, entitled METHOD FOR TAGGING IMAGES, filed May 9, 2005; both of the aforementioned priority applications being hereby incorporated by reference in their entirety.

This application is a continuation-in-part of U.S. patent application Ser. No. 11/246,589, entitled SYSTEM AND METHOD FOR RECOGNIZING OBJECTS FROM IMAGES AND IDENTIFYING RELEVANCY AMONGST IMAGES AND INFORMATION, filed on Oct. 7, 2005; which claims benefit of priority to U.S. Provisional Patent Application No. 60/679,591, entitled METHOD FOR TAGGING IMAGES, filed May 9, 2005; both of the aforementioned priority applications being hereby incorporated by reference in their entirety.

This application is a continuation-in-part of U.S. patent application Ser. No. 11/246,434, entitled SYSTEM AND METHOD FOR PROVIDING OBJECTIFIED IMAGE RENDERINGS USING RECOGNITION INFORMATION FROM IMAGES, filed on Oct. 7, 2005; which claims benefit of priority to U.S. Provisional Patent Application No. 60/679,591, entitled METHOD FOR TAGGING IMAGES, filed May 9, 2005; both of the aforementioned priority applications being hereby incorporated by reference in their entirety.

TECHNICAL FIELD

The disclosed embodiments relate generally to a computer-implemented method for performing similarity searches, such as of persons and faces.

BACKGROUND

Digital photography has become a consumer application of great significance. It has afforded individuals convenience in capturing and sharing digital images. Devices that capture digital images have become low-cost, and the ability to send pictures from one location to the other has been one of the driving forces in the drive for more network bandwidth.

Due to the relative low cost of memory and the availability of devices and platforms from which digital images can be viewed, the average consumer maintains most digital images on computer-readable mediums, such as hard drives, CD-

2

Roms, and flash memory. The use of file folders are the primary source of organization, although applications have been created to aid users in organizing and viewing digital images. Some search engines, such as GOOGLE, also enables users to search for images, primarily by matching text-based search input to text metadata or content associated with images.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates a simplified system for performing similarity searching of persons using various kinds of information, according to an embodiment of the invention.

FIG. 2 illustrates components for use in enabling similarity searches of persons, according to one or more embodiments of the invention.

FIG. 3 illustrates a method for enabling a similarity search to be performed on an image of a face, according to an embodiment of the invention. FIG. 1 illustrates

DETAILED DESCRIPTION

Embodiments described herein provide a system and method for performing similarity searches or comparisons of people. In particular, embodiments described herein provide for performing similarity searching to compare images of persons and faces against those of other in order to find persons who are similar in appearance. Face similarity searching, in particular, may be used to identify faces of persons who look like one another.

Numerous usages for person or face similarity search exist. For example, on a social network site, face similarity can be used to cluster individuals who are deemed to look like on another, as a means of introduction. On an online dating site, similarity searching can be used to enable a customer to identify persons in a dating pool that have a specific type of appearance or visual characteristic that the customer prefers. For example, a person may seek other persons who resemble a favorite movie star. A face similarity engine may also be used to identify persons who look like one another for purposes of amusement.

One or more embodiments enable face similarity operations to be performed, where a face in an image is used to generate search criteria from which a result of similar faces is programmatically determined. In one embodiment, a person is identified from an image. In particular, a face of a person is identified using face detection algorithms. Text and metadata associated with the image of the person are also identified. A similarity search is then performed using the image of the person in order to identify images of other persons that are similar in appearance to the person in the image. One or more embodiments further provide that at least some of the text and metadata are used to determine one or more classifications for the person in the image. The determined classifications are used as part of the similarity search.

For example, the determined classifications may be used to filter a search result, or enhance determinations made about the image when the image is analyzed.

One or more embodiments also provide a system for determining facial similarity. In an embodiment, the system includes an analysis module that is configured to identify (i) a face from an image, and (ii) at least one of text or metadata associated with the face of the image. Additionally, the system may include a characteristic determination module and a comparison module. The characteristic determination module is configured to identify one or more biographical classifications of the face based at least in part on the at least one of

the text or metadata associated with the face of the face. The comparison module is configured to compare a query image input of the face with a collection of images of other faces in order to identify one or more faces in the collection that are determined as being similar to the face of the query image input. The query image input comprises image data representing the face and the one or more biographical classifications determined about the face using at least the text and metadata.

As used herein, the term “image data” is intended to mean data that corresponds to or is based on discrete portions of a captured image. For example, with digital images, such as those provided in a JPEG format, the image data may correspond to data or information about pixels that form the image, or data or information determined from pixels of the image. Another example of “image data” is signature or other non-textual data that represents a classification or identity of an object, as well as a global or local feature.

The terms “recognize”, or “recognition”, or variants thereof, in the context of an image or image data (e.g. “recognize an image”) is meant to mean that a determination is made as to what the image correlates to, represents, identifies, means, and/or a context provided by the image. Recognition does not mean a determination of identity by name, unless stated so expressly, as name identification may require an additional step of correlation.

As used herein, the terms “programmable”, “programmatically” or variations thereof mean through execution of code, programming or other logic. A programmatic action may be performed with software, firmware or hardware, and generally without user-intervention, albeit not necessarily automatically, as the action may be manually triggered.

One or more embodiments described herein may be implemented using programmatic elements, often referred to as modules or components, although other names may be used. Such programmatic elements may include a program, a subroutine, a portion of a program, or a software component or a hardware component capable of performing one or more stated tasks or functions. As used herein, a module or component, can exist on a hardware component independently of other modules/components or a module/component can be a shared element or process of other modules/components, programs or machines. A module or component may reside on one machine, such as on a client or on a server, or a module/component may be distributed amongst multiple machines, such as on multiple clients or server machines. Any system described may be implemented in whole or in part on a server, or as part of a network service. Alternatively, a system such as described herein may be implemented on a local computer or terminal, in whole or in part. In either case, implementation of system provided for in this application may require use of memory, processors and network resources (including data ports, and signal lines (optical, electrical etc.), unless stated otherwise.

Embodiments described herein generally require the use of computers, including processing and memory resources. For example, systems described herein may be implemented on a server or network service. Such servers may connect and be used by users over networks such as the Internet, or by a combination of networks, such as cellular networks and the Internet. Alternatively, one or more embodiments described herein may be implemented locally, in whole or in part, on computing machines such as desktops, cellular phones, personal digital assistants or laptop computers. Thus, memory, processing and network resources may all be used in connection with the establishment, use or performance of any

embodiment described herein (including with the performance of any method or with the implementation of any system).

Furthermore, one or more embodiments described herein may be implemented through the use of instructions that are executable by one or more processors. These instructions may be carried on a computer-readable medium. Machines shown in figures below provide examples of processing resources and computer-readable mediums on which instructions for implementing embodiments of the invention can be carried and/or executed. In particular, the numerous machines shown with embodiments of the invention include processor(s) and various forms of memory for holding data and instructions. Examples of computer-readable mediums include permanent memory storage devices, such as hard drives on personal computers or servers. Other examples of computer storage mediums include portable storage units, such as CD or DVD units, flash memory (such as carried on many cell phones and personal digital assistants (PDAs)), and magnetic memory. Computers, terminals, network enabled devices (e.g. mobile devices such as cell phones) are all examples of machines and devices that utilize processors, memory, and instructions stored on computer-readable mediums.

Overview

FIG. 1 illustrates a simplified system for performing similarity searching of persons using various kinds of information, according to an embodiment of the invention. In an embodiment, a similarity search engine **110** is adapted or programmed to perform similarity searches of images, and of persons in particular. In an embodiment, a query image input **102** is used as a basis of comparison for finding other persons that have an appearance that is programmatically determined to be similar. Thus, search criteria may be generated to correspond to the query image input **102**. The query image input **102** may correspond to an image of a face of a person that is to serve as the basis for comparison. For example, a user of a social network site may use his own image as input, for comparison and identification of other persons who share similarities. The engine **110** may use query image input **102** to generate result images **114**, comprising a set of images that are programmatically determined to be similar to the face of the query image input **102**. An embodiment of FIG. 1 assumes engine **110** includes or accesses a collection of images **120** in order to generate or identify the result images **114**.

Different types of similarity searches are possible. In one embodiment, the query image input **102** is used to identify classifications or types of visual characteristics such as hair or eye color, or facial type. In another embodiment, the query image input **102** is based on recognition signatures, which can substantially uniquely identify persons. In the latter case, a feature vector that corresponds to a signature of a face may be compared against, for example, an index or library of other signatures for other faces. Vector distance algorithms may be used to compare one face against another face. Such feature vector comparisons of faces is described in parent U.S. patent application Ser. No. 11/246,742, entitled SYSTEM AND METHOD FOR ENABLING THE USE OF CAPTURED IMAGES THROUGH RECOGNITION, filed on Oct. 7, 2005.

As an alternative or addition to determining feature vectors that are signature identifiers of a person or a face, one or more embodiments provide for use of computer vision and analysis to detect additional visual features from the face of the query image input **102**. The terms “face similarity” or “facial similarity” refer the act of retrieving a set of pictures of “result” faces which look similar to a given “query” face picture. In

one embodiment, face similarity relies on visual features extracted from the query face, matching those features to similar features of the result faces. Those features can include skin tone, hair color, hair length, or a face model such as those used for face recognition (PCA (Principal Component Analysis), or LDA (Linear Discriminant Analysis)) as described in U.S. patent application Ser. No. 11/246,742, entitled SYSTEM AND METHOD FOR ENABLING THE USE OF CAPTURED IMAGES THROUGH RECOGNITION, filed on Oct. 7, 2005.

In one embodiment, eye color can be obtained by applying eye detection, followed by looking at color profiles around the detected eye. In another embodiment, hair color and length can be obtained by applying segmentation first. Segmentation groups face regions into three classes: (i) skin, (ii) hair, and (iii) background. A hair color may be obtained by determining color features such as color histogram, or dominant color descriptor on the pixels that are assigned as part of hair within segmentation. Similarly, the hair length can be obtained by looking at the span of the pixels that are assigned as part of the hair by segmentation.

As another alternative or addition, another facial feature that may be used by engine 110 to perform similarity searching may correspond to a type of face shape contained by the face of the query image input 102. For instance, the height and the width of a face, as well as a generalization or quantitative description of an overall head-shape (elongated or round shape) may provide another basis for identifying results 114. This information can be extracted using various means. In one embodiment, segmentation output is used in analyzing the query image input 102. The width and height can be determined using the span of the pixels that are assigned as skin during segmentation. In another embodiment, a classifier-based approach can be used. A training set of elongated and round faces is collected. As an example, a learning algorithm such as Adaboost, or support vector classifier or nearest neighbor classifier can be used to learn how to classify a face as elongated or round based on the training set.

As another alternative or addition, another facial feature that may be used by engine 110 to perform similarity searching is skin color. As described above, a segmentation output can be used to determine the skin color. The skin color can be obtained by getting color features such as color histogram, or dominant color descriptor on the pixels that are assigned as part of skin within segmentation.

As another alternative or addition, another facial feature that may be used by engine 110 to perform similarity searching is a classification corresponding to whether the person of the query image input 102 is wearing eyeglasses. In one embodiment, a classifier-based approach can be used. A training set of faces with and without glasses is collected. As an example, a learning algorithm such as Adaboost, or support vector classifier or nearest neighbor classifier can be used to learn how to classify a face as with or without glasses based on the training set.

As another alternative or addition, another facial feature that may be used by engine 110 to perform similarity searching is a classification corresponding to whether the person of the query image input 102 has facial hair, such as a mustache or beard. Numerous algorithms may be used to detect the facial hair. In one embodiment, key points are detected in the face. Such key points may correspond to the tip of the nose, or the mouth corners. Then, the pixels between the mouth and the nose are analyzed. The color and the texture of this region can be compared to an obviously skin region, such as the forehead, nose, or cheeks. The difference between the color and texture is an indication of a mustache. In another embodi-

ment, a classifier-based approach can be used. A training set of faces with and without facial hair is collected. As an example, a learning algorithm such as Adaboost, or support vector classifier or nearest neighbor classifier can be used to learn how to classify a face as with or without facial hair based on the training set.

Embodiments described herein further recognize that certain classifications about a person's appearance may also be inferred from other sources of information, rather than the query image input 102. In particular, embodiments recognize that biographic information may yield clues to classifications about a person's appearance, and these clues may enable similarity searching to be performed in a manner that a viewer deems to be more reliable. For example, programmatic analysis of images of faces may be unreliable in determining gender.

Embodiments described herein recognize that visual features are not always representative of classifications that people would consider important when viewing similarity searches. Specifically, the use of visual features in similarity searching may not always be reliable in determining ethnicity, age classification, or gender. For example, on a social network, a person seeking a similarity match to a male is not interested in seeing a female. As another example, similarity matching amongst persons of different ethnicity may not result in matches that the human eye would consider similar. Moreover, the accuracy of some inferences of classification may be hindered if the query image input 102 has low quality or contains ambiguous cues (presence of sunglasses, hat, etc.)

One or more embodiments described herein assume that the query face and/or images in the collection 120 the provide the result images 114 have a known identity or extraneous biographical information 104 attached or associated to them. Accordingly, the biographical information 104 may have the role of forming a criteria or parameter by which images are filtered when determining whether images from collection 120 or sufficiently similar. In such embodiments, biographical information 114 may be determined from, for example, user-input and/or the context of environment in which the image is placed. For example, on a social networking or match making site, the biographical information 114 may have been provided by the user when his or her account or profile were established. In such embodiments, the biographical information may be retrieved from the text of the person's profile.

As described herein, such biographical information 104 may take several forms, some of which can be used independently or in conjunction with each other to create additional features to assist in enhancing similarity matching algorithms.

In one embodiment, the biographical information 104 and its relationship to the face of the query image input 102 can be obtained through a combination of factors or processes, such as through the use of a face recognition system which associates the set of recognized faces to identities known to the system. According to an embodiment, elements of an identity can incorporate one or more of the following: (i) the first name of the person; (ii) the last name of the person; (iii) external biographical data about the person: gender, age, ethnicity, place of living, hair color, style and length; (iv) a nickname for that person ("cutechick", "dad"); (v) a set of example face images for that person, possibly tagged with the date at which the picture was taken; (vi) the person's relationship to a social network comprising his/her friends and/or family members; (vii) a geographically labeled photo album

belonging to that person; and (viii) a location obtained from the IP address of the computer that he/she uses or uploads his photographs to a server.

Some or all of the biographical information **104** may be used by the engine **110** in order to perform similarity searching of a face and/or person in the query image input **102**. In one embodiment, the resulting images **114** may be determined by using the biographical information to either (i) filter an initial set of resulting images that are identified from similarity searching the collection of images **120**, or (ii) by filtering the collection of images **120** before performing the similarity searching. As an addition or alternative, biographical information **114** may be used to rank images of result **114**, and/or to weight parameters representing visual similarities (e.g. hair color, face type) when the similarity search is performed.

System for Analyzing Content Items Carrying Images

FIG. 2 illustrates components for use in enabling similarity searches of persons, according to one or more embodiments of the invention. A system such as described with an embodiment of FIG. 2 may be used to provide some or all of the functionality of engine **110**, as well as to provide data (query image input **102** and collection **120**) used by engine **110**.

Accordingly, a system **200** may include modules that correspond to analysis **215**, characteristic determination **230**, and comparison **245**. The analysis module **215** may include sub-modules or components of feature extraction **210** and text/metadata extraction **220**. The input for system **200** may include records **202** that are associated with individuals. For each person, record(s) **202** may include a set of one or more images and text and/or metadata. The input records **202** may be used as part of a backend process to build the collection of records **120** (FIG. 1) that is searched. Additionally, input records **202** may correspond to the query input image **102** (FIG. 1). System **200** may process records **202** as query input image **102** on either a backend process or as a front end process (e.g. on-the-fly).

In an embodiment, system **200** outputs a profile data set **230** for individual persons. The profile data sets **230** are searched for similarities against the query input image **102**. According to an embodiment, the profile data set **230** may include (i) image data that represents the image of the record **202**, such as images in the form of features as extracted by the extraction module **210**; (ii) classifications of gender, ethnicity, age or other biographical classification; and (iii) optionally an identity of the person that is the subject of the record. In one embodiment, the profile data set **230** of a given person or face is created and/or retrieved as the query image input **102** when similarities are desired for that face or person.

The comparison module **245** may perform the operations of comparing the profile data set **230** for the query image input **102** (whether retrieved from data store or determined on the fly) against the profile data sets **230** of images in the collection **120**. In making a determination of similarity, various parameters may be used as criteria in determining whether individual records or images of collection **120** satisfy a similarity threshold for the query image input **102**. One or more embodiments also rank any images in the collection **120** that satisfy the similarity threshold, meaning those images that are deemed most similar may rank higher than other images that satisfy the threshold but are less similar. In one implementation, higher ranked images are displayed first or otherwise more prominently.

In an embodiment, the input record **202** may correspond to one or more of an image, a collection of images, labels or tags provided with the image, and/or profile information provided in connection with a context or source of that image. For

example, system **200** may be implemented for individuals who upload or submit a collection of personal images as part of a photo-sharing site. In one embodiment, the images of the input record **202** have not previously been processed or recognized, and feature extraction **210** identifies image data **212** that corresponds to features of the person or persons in the images of the records **202**. As an alternative, the images of the input records **202** may be associated with, for example, previously determined vector signatures that are then identified and used by system **200**.

The text/metadata extraction **220** identifies and/or extracts text or metadata information that includes biographical information **222**. However, embodiments recognize that not all extracted text/metadata may be biographical information **222**. As such, extracted words or phrases may initially be viewed as candidates for determining subsequent classifications. The biographical information **222**, along with image data **212** (if present), is used by the characteristic determination **230** to generate the profile data set **240** for a person. One or more embodiments provide that the characteristic determination **230** determines gender, ethnicity, and/or age classification.

Gender: In one embodiment, gender component **232** makes a gender determination for a subject of a person in a given input record **202** using a combination of biographical information **222** and image data **212**. The biographical information **222** used may correspond to a first name of the person, or a nickname derived from label or text in other content (e.g. name of person who created a file or is named on a blog of a social network). For example, certain names or labels may be associated with one gender or another (e.g. "Mark" for male, "Emily" for female). Other biographical data may also be used (e.g. the image of the person is labeled "I'm pregnant"). The image data **212** may correspond to pixels or image elements of the image in the input record **202** being subjected to a gender classifier. In one embodiment, a person provides numerous input images as part of record(s) **202**, and the gender classifier is applied to each face in a set of example faces (that are determined to be of the same person), combined using, for example, a voting scheme.

Ethnicity: The ethnicity component **234** of the characteristic determination **230** may use biographical information **222** to programmatically and/or automatically learn or determine an ethnicity of a person. Ethnicity determination may use biographical information such as (i) a combination of the first and last name of that person; (ii) ethnicity of people in the person's social network; (iii) the most frequent geographic location of the person's pictures; (iv) an ethnicity classifier applied to the image data **212** representing each face in a set of example faces, combined for using, for example, a voting scheme. The first name and the last name can be used as a whole, or they can be syllables of the first name or the second name. In the latter case, the words can be broken into syllables along with position markers: beginning, middle, end of word. In one embodiment, ethnicity statistics may be collected for each syllable. A naive Bayes classifier may be used to come up with a posterior for each ethnicity.

Age: An age component **232** of the characteristic determination **230** may automatically learn an age classification of a person that is the subject of records **202**, using biographical information corresponding to, for example, (i) the first name or nickname of that person (for example: "dad" implies an adult . . .); (ii) the age of persons in the person's social network; (iii) the span of image capture dates in an image library provided by that person (for example, if that person has pictures taken 20 years ago, then it implies an adult); and (iv) an age group classifier applied to the image data **212**

representing each face in an example set, combined taking into account aging based on the picture timestamps.

Classifiers that operate on image data **212** to determine gender, ethnicity, and age classification are described in more detail with, for example, U.S. patent application Ser. No. 11/246,742, entitled SYSTEM AND METHOD FOR ENABLING THE USE OF CAPTURED IMAGES THROUGH RECOGNITION, filed on Oct. 7, 2005.

One or more embodiments also provide for use of an optimization module **244** that implements one or more optimization functions or processes for use with system **200**. In one embodiment, the optimization module **230** includes functionality for automatically determining a 'goodness' (or degree of suitability for image searching) of an image of a face. In one embodiment, the optimization module discards images that are deemed unsuitable for the similarity searching. The determination may be made on a so-called goodness measure. In one implementation, a goodness measure may quantify clarity, lighting, and pose in determining whether a given image is usable in either the collection **120** (FIG. 1) or as the query image input **102** (FIG. 1). A goodness measure can also be made specific to a set of images of a particular person or to a classification of a type of person using learned algorithms. In such cases, the goodness measure may be determined automatically using regression techniques, such as least square fitting to linear and quadratic functions of visual features. As an example, any types of feature vectors can be used for this purpose. For instance, bad/good lighting classifiers, bad/good pose classifiers, face appearance models (PCA, LDA, etc) can all be used to learn a generic goodness metric for each face.

In an embodiment, the optimization module **244** may also be configured to automatically determine an optimal set of visual features to use to drive a similarity search. Such an embodiment recognizes that it is more difficult to find similarity results for an image of a face that, for example, has a non-frontal pose, bad lighting, has the person/face off in the distance, is blurry, or otherwise partially occludes the subject of the image. For a given set of images for a person or class, the optimizer may execute functionality for determining which subset of examples in a set of face examples to use to extract features. This determination may be based on: (i) the quality of the face pictures, (ii) the distance in time to the query image to ensure that the selected query face is not too dissimilar in terms of age and facial features (such as facial hair or haircut), (iii) a pose, and (iv) lighting variations on a face of an image.

Additionally, optimizer **244** may incorporate metrics for programmatically learning a degree of ethnic/demographic relationship between people based on their names. For example, two people with similar names have a better chance of (i) being part of the same ethnic group (some Asian countries have little variability in their last name); (ii) being of the same gender (same first name); (iii) being of similar age (same first name); (iv) being part of the same family (same last name); and (v) being the same person (same first and last name). As a result, a measure of the degree of closeness between two names, which can be based for example on an edit distance, is an additional hint that the faces of these people might be perceived as more similar. The optimizer **244** may incorporate these relationships in the profile data sets **240** for subsequent use. Alternatively, the characteristic determination may incorporate the functionality described in this paragraph when analyzing the record **202**, either on the back-end or front-end and on-the-fly.

Embodiments recognize that some records **202** incorporate identity information, meaning information (e.g. full name) that uniquely identifies that person. This information is useful

for a variety of purposes. However, if identity information is not available for either the query or result images, automatic labeling can be used as a fall back mechanism. Automatic labeling improves the quality of the similarity features, thereby simplifying indexing and improving the result quality, especially for low quality query images.

FIG. 3 illustrates a method for enabling a similarity search to be performed on an image of a face, according to an embodiment of the invention. A method such as described may be implemented using, for example, a system such as described with FIG. 1 or FIG. 2. As such, reference to elements of an embodiment of FIG. 2 is made for purpose of illustrating a suitable component for performing a step or sub-step being described.

In a step **310**, the query input image **102** (FIG. 1) is determined or identified. In one embodiment, a face in the image is detected, and an identity is established for the face in the image. This identity may be determined either through user-tagging or through a face recognition process (which can be semi-supervised by the user). A suitable facial recognition system or process is described in U.S. patent application Ser. No. 11/246,742, entitled SYSTEM AND METHOD FOR ENABLING THE USE OF CAPTURED IMAGES THROUGH RECOGNITION, filed on Oct. 7, 2005.

In step **320**, biographical information for the face of the query image input is determined or retrieved. The text/metadata extraction module **220** may be used to determine the biographical information on-the-fly. Alternatively, the query image input **102** may already have that information associated with it. From the biographical information available for that face, one or more embodiments provide that the person's identity is optionally established (if not already known). Additionally, as described with an embodiment of FIG. 2, a gender, ethnicity and age classification of a person in the query image input **102** is determined. The output of engine **110** may be restricted to provide results which share at least some (if not all) similar biographical information **222**.

Step **330** provides that (i) images depicting a face of a person with the same identity as the query image input **102** are identified, (ii) from the identified images, a subset ('Set A') of faces which are the best query faces are identified. In one embodiment, the similarity search is performed using the subset of images of the same person. As previously described, a good subset could be a set of frontal shots which are close in time to the original query image, or faces with high 'goodness' score as described in the earlier section.

Step **340** provides that a similarity search is performed with the subset of images of the query image input **102**, taking into account the biographical information **222** associated with the person or identify of the input. From collection **120**, a result set of faces is identified, where persons of the result set share some or all (or have similar) biographical information **222**. These persons may also have faces that are deemed to be similar to that of the query image input **102**. The visual similarity may be performed using, for example, a PCA model in combination with models for facial hair, glasses, hair color and haircut. A weighted distance combination can be used using these features. The weighting itself can be learnt using statistical classification techniques such as Linear Discriminant Analysis (LDA). The retrieval can be performed using a nearest neighbor algorithm which selects a subset of the faces expected to be the closest to the target set of faces, followed by shortest distance search within that subset. The outcome of this process may correspond to the result images **114**, or otherwise a list of result faces which are most similar to the query face.

11

As an addition or alternative step, one or more embodiments provide for a method such as described to further determine an identity of persons shown in the result image set **114**. If a person has multiple images in the result set **114**, it is more likely that the two persons (i.e. the person of the query image input **102** and the person having multiple images depicted in the result set **144**) or the same person.

As another addition or alternative, one or more embodiments provide for reordering images in the result set **114** based on a combination of the similarity distance and the degree of closeness of the names of the people they belong to. Thus, the name of the person may provide key biographic information **222** for use in the similarity searching.

As another addition or alternative, one or more embodiments provide finding identities of persons in the result set **114**, then scanning the collection for images of those identified persons sharing the same pose of the face or person of the query image input **102**. Rather than return the original image, the image with the matching pose of the person deemed to be similar is returned. This image may look more similar to the user, given the matching pose.

In another embodiment, a human team may review the results of visual features as extracted or determined by system **200**. As an example, the results of ethnicity can be reviewed and corrected by human beings. U.S. Patent Application No. 60/864,781 describes a manual editor interface (“manual enrichment”) that presents recognition or image analysis images to editors in cascade (numerous panels shown at once, with each panel containing the subject image and the determined information about that image). The editor or human is offered to uncheck the determined result if it is not correct. For example, if an Asian person is marked white as a result of recognition performed on the face of the image, the editor may simply uncheck “Caucasian” in a panel where the Asian person is shown. One or more embodiments provide for a fast editor user-interface. For instance, the user-interface may group images of persons in one cascade or sheet, that are all deemed blonde and male. A dozen or tens of images may be listed. The editor simply marks (or unmarks) the image of the person that is not blonde and male.

Accordingly, one or more embodiments provide for a data flow that includes establishing an identify of a given face in the query image input **102**. The identity may be determined either through user tagging or through a face recognition process (which can be semi-supervised by the user).

Next, computer vision algorithms may be executed on the test images to calculate the visual features, such as gender, ethnicity, hair color, hair length, eye color, with/without eye glasses.

An editor interface may be provided to review the results. As described above, the results may be reviewed in groups or clusters.

From the biographical information available for a face in an image, one or more embodiments provide for establishing the person’s identity (if not already available), gender, and age characteristics.

From the set of faces associated to the same identity as the query image input **102**, embodiments determine a subset of faces that match both visually and with biographical information. As previously described, a good subset could be a set of frontal shots which are close in time to the original query image, or faces with high ‘goodness’ score as described in the earlier section.

Using this new set of query faces, one or more embodiments determine, from within the set of faces which share similar biographical data as well as visual features, which faces are the closest based on visual features. The determina-

12

tion may be made through, for example, a PCA model in combination with models for facial hair, glasses, hair color and haircut. A weighted distance combination can be used using these features. The weighting itself can be learnt using statistical classification techniques such as Linear Discriminant Analysis (LDA). The retrieval can be performed using a nearest neighbor algorithm which selects a subset of the faces expected to be the closest to the target set of faces, followed by shortest distance search within that subset. The outcome of this process is a list of result faces which are most similar to the query face.

Numerous variations and options, such as described with an embodiment of FIG. **3** may be implemented.

Any of the embodiments described with FIG. **1** thru FIG. **3** may be performed by computers, including general purpose computers, connected (to a network or the Internet) computers, or combinations of client-server computers and/or peer-to-peer terminals. In one embodiment, for example, system **200** is provided on a server, and accessed by a user through a web interface. However, alternatives are possible, including use of standalone computers to provide system **200**.

ALTERNATIVE EMBODIMENTS

While embodiments described herein provide for use of biographical information from metadata and text data, biographical image in the form of text can be determined from the contents of the image. For example, an image of a person may show text imprint on a shirt or on an associated sign in the image. This text may be detected, then recognized and used to decipher clues about classifications (e.g. gender, ethnicity and age classification) of the person. U.S. patent application Ser. No. 11/246,742, entitled SYSTEM AND METHOD FOR ENABLING THE USE OF CAPTURED IMAGES THROUGH RECOGNITION, filed on Oct. 7, 2005; describes techniques for detecting, recognizing and using such text from images of persons.

It is contemplated for embodiments of the invention to extend to individual elements and concepts described herein, independently of other concepts, ideas or system, as well as for embodiments to include combinations of elements recited anywhere in this application. Although illustrative embodiments of the invention have been described in detail herein with reference to the accompanying drawings, it is to be understood that the invention is not limited to those precise embodiments. As such, many modifications and variations will be apparent to practitioners skilled in this art. Accordingly, it is intended that the scope of the invention be defined by the following claims and their equivalents. Furthermore, it is contemplated that a particular feature described either individually or as part of an embodiment can be combined with other individually described features, or parts of other embodiments, even if the other features and embodiments make no mention of the particular feature. This, the absence of describing combinations should not preclude the inventor from claiming rights to such combinations.

What is claimed is:

1. A computer-implemented method for determining face similarity, the method comprising:
 - using one or more processors to perform steps comprising: detecting a plurality of persons collectively depicted in a collection of images;
 - performing image analysis for individual persons that appear in one or more images in the collection, including determining a plurality of visual features and determining gender, age, or racial classifications for at least some of the persons depicted in the collection from perfor-

13

mance of the image analysis, wherein the plurality of visual features comprise skin tone, hair color, hair length, or face type;
 storing information determined from performing image analysis for the individual persons;
 receiving one or more inputs from the user that (i) include an image of a person, and (ii) identify one or more gender, age, or racial classifications; and
 performing a similarity search using said one or more inputs, in order to identify images of other persons depicted in one or more images of the collection that are both (i) similar in appearance to the person in the image input by the user, and (ii) match the gender, age, or racial classifications identified by the one or more inputs;
 wherein performing the similarity search includes determining similarities between a plurality of visual features of the person depicted in the image input by the user and the plurality of visual features of persons depicted in the one or more images of the collection, wherein the determined similarities are weighted based upon the gender, age, or racial classifications identified by the one or more inputs.

2. The method of claim 1, wherein determining gender, age or racial classifications for at least some of the persons depicted in the collection includes determining gender, age, or racial information about the person in the image, at least in part, by performing analysis of text or metadata associated with the collection of images.

3. The method of claim 1, wherein performing the similarity search includes formulating a search query to include image data that represents one or more visual characteristics of a face of the person included in the one or more inputs.

4. The method of claim 2, wherein determining gender, age, or racial classifications for at least some of the persons further comprises identifying a label or a tag provided with the image.

5. The method of claim 2, wherein determining gender, age, or racial classifications for at least some of the persons further comprises identifying a text contained as part of the image.

6. A system for determining face similarity, the system comprising:
 an analysis module that is configured to perform image analysis to identify, for individual images in a collection

14

of images, (i) a face from the image, and (ii) at least one of text or metadata associated with the face of the image;
 a characteristic determination module that is configured to identify, for individual images in the collection, (i) a plurality of visual features, and (ii) one or more gender, age, or racial classifications based at least in part on image analysis performed by the analysis module;
 a data store to store information determined from the image analysis module and the characteristic determination module;
 a comparison module that identifies a query comprising (i) an image input of a face of a given person, the image input being received from a user, and (ii) a gender, age, or racial classification as determined from the image input or from other input of the user;
 wherein the comparison module performs a similarity search by comparing the query with information in the data store in order to identify one or more faces of persons other than the given person in the collection of images that are determined as being both (i) similar to the face of the query image input, and (ii) of a same gender, age, or racial classification of the query;
 and wherein the similarity search includes determining similarities between a plurality of visual features of the face of the query image input and the plurality of visual features of persons depicted in one or more images of the collection, wherein the determined similarities are weighted based upon the gender, age, or racial classification for the face of the query image input.

7. The system of claim 6, wherein the characteristic determination module is configured to determine any of the one or more gender, age, or racial classifications using a combination of the text and metadata and any image data representing the face of the image.

8. The system of claim 6, wherein the characteristic determination module identifies at least one of text or metadata associated with the image by identifying a text contained in a file that includes the image of the person.

9. The system of claim 6, wherein the characteristic determination module identifies at least one of text or metadata associated with the image by identifying a label or a tag provided with the image.

* * * * *